

750W



CPR-7511-1M1

- Dimension : 185 x 73 x 40 mm (D x W x H)
- Total Max Power : 750W @ 100 - 240Vac

INPUT SPECIFICATIONS

| | |
|-----------------|--|
| Input voltage | 90 - 264Vac |
| Input frequency | 47 - 63Hz |
| Input current | 100 - 127V / 9.3 - 7.2A 200 - 240V / 4.6 - 3.9A |

GENERAL SPECIFICATIONS

| | |
|--------------|--|
| Hold-up time | 11ms @ 70% Load |
| Efficiency | 94% @ 50% Load |
| MTBF | 200,000 hours at 100% load and 25 degree C |

ENVIRONMENTAL SPECIFICATIONS

| | |
|-------------------|----------------------------|
| Temperature | 0 to 50 degree C Operating |
| Altitude | 16,400 feet Operating |
| Relative humidity | 20% to 85% RH Operating |

OUTPUT SPECIFICATIONS

| | | |
|----------------|----------|----------|
| Voltage | +12V | +12Vsb |
| Regulation | ±5% | ±5% |
| Max Load | 60.4A | 2.1A |
| Ripple & Noise | 120mVp-p | 120mVp-p |



FEATURES

- 80 PLUS Platinum
- Internal OR'ing
- Digital Power Supply
- Smart Ride Through
- Intel Standard CRPS Form Factor
- Active Power Factor Correction
- High Power Density 24.8 W/in³
- Closed Loop System Protection (CLST)
- Automatic Firmware Update
- Support PMBus 1.3
- N+1 Redundant
- Cold Redundancy
- Black Box Recorder



UL , cUL , CB , CE , CCC , BSMI , FCC class A , CISPR Class A , RoHS

